

# Package: **tbm** (via r-universe)

October 17, 2024

**Title** Transformation Boosting Machines

**Version** 0.3-6

**Date** 2024-04-17

**Description** Boosting the likelihood of conditional and shift transformation models as introduced in [doi{10.1007/s11222-019-09870-4}](https://doi.org/10.1007/s11222-019-09870-4).

**Depends** mlt ( $\geq$  1.0-6), mboost ( $\geq$  2.8-2)

**Imports** variables, basefun, sandwich, coneproject, methods

**Suggests** TH.data ( $\geq$  1.0-9), tram ( $\geq$  0.2-3), survival, partykit, lattice, latticeExtra, knitr, colorspace, gamlss.data, trtf

**VignetteBuilder** knitr

**URL** <http://ctm.R-forge.R-project.org>

**License** GPL-2

**Repository** <https://trafo-universe.r-universe.dev>

**RemoteUrl** <https://github.com/r-forge/ctm>

**RemoteRef** HEAD

**RemoteSha** bf68b8828a608dd9499a74af1bfdb746420dbc03

## Contents

ctmboost . . . . .	2
stmboost . . . . .	3

<b>Index</b>	<b>5</b>
--------------	----------

ctmboost

*Likelihood Boosting for Conditional Transformation Models***Description**

Employs maximisation of the likelihood for estimation of conditional transformation models

**Usage**

```
ctmboost(model, formula, data = list(), weights = NULL,
         method = quote(mboost::mboost), ...)
```

**Arguments**

<code>model</code>	an object of class <code>mlt</code> as returned by <code>mlt</code> .
<code>formula</code>	a model formula describing how the parameters of <code>model</code> depend on explanatory variables, see <code>mboost</code> .
<code>data</code>	an optional data frame of observations.
<code>weights</code>	an optional vector of weights.
<code>method</code>	a call to <code>mboost</code> , <code>gamboost</code> , or <code>blackboost</code> .
<code>...</code>	additional arguments to <code>method</code> .

**Details**

The parameters of `model` depend on explanatory variables in a possibly structured additive way (see Hothorn, 2020). The number of boosting iterations is a hyperparameter which needs careful tuning.

**Value**

An object of class `ctmboost` with `predict` and `logLik` methods.

**References**

Torsten Hothorn (2020). Transformation Boosting Machines. *Statistics and Computing*, **30**, 141–152.

**Examples**

```
if (require("TH.data") && require("tram")) {
  data("bodyfat", package = "TH.data")

  ### estimate unconditional model
  m_mlt <- BoxCox(DEXfat ~ 1, data = bodyfat, prob = c(.1, .99))
  ### get corresponding in-sample log-likelihood
  logLik(m_mlt)

  ### estimate conditional transformation model
```

```

bm <- ctboost(m_mlt, formula = DEXfat ~ ., data = bodyfat,
              method = quote(mboost::mboost))
### in-sample log-likelihood (NEEDS TUNING OF mstop!)
logLik(bm)

### evaluate conditional densities for two observations
predict(bm, newdata = bodyfat[1:2,], type = "density")
}

```

---

stmboost

*Likelihood Boosting for Shift Transformation Models*


---

### Description

Employs maximisation of the likelihood for estimation of shift transformation models

### Usage

```

stmboost(model, formula, data = list(), weights = NULL,
          method = quote(mboost::mboost), mltargs = list(), ...)

```

### Arguments

model	an object of class <code>mlt</code> as returned by <code>mlt</code> .
formula	a model formula describing how the parameters of <code>model</code> depend on explanatory variables, see <code>mboost</code> .
data	an optional data frame of observations.
weights	an optional vector of weights.
method	a call to <code>mboost</code> , <code>gamboost</code> , or <code>blackboost</code> .
mltargs	a list with arguments to be passed to <code>mlt</code> .
...	additional arguments to <code>method</code> .

### Details

The parameters of `model` depend on explanatory variables in a possibly structured additive way (see Hothorn, 2020). The number of boosting iterations is a hyperparameter which needs careful tuning.

### Value

An object of class `stmboost` with `predict` and `logLik` methods.

### References

Torsten Hothorn (2020). Transformation Boosting Machines. *Statistics and Computing*, **30**, 141–152.

**Examples**

```
if (require("TH.data") && require("tram")) {
  data("bodyfat", package = "TH.data")

  ### estimate unconditional model
  m_mlt <- BoxCox(DEXfat ~ 1, data = bodyfat, prob = c(.1, .99))
  ### get corresponding in-sample log-likelihood
  logLik(m_mlt)

  ### estimate conditional transformation model
  bm <- stmboost(m_mlt, formula = DEXfat ~ ., data = bodyfat,
                method = quote(mboost::mboost))
  ### in-sample log-likelihood (NEEDS TUNING OF mstop!)
  logLik(bm)

  ### evaluate conditional densities for two observations
  predict(bm, newdata = bodyfat[1:2,], type = "density")
}
```

# Index

- \* **models**
  - ctmboost, 2
  - stmboost, 3
- \* **nonlinear**
  - ctmboost, 2
- \* **nonlinear**
  - stmboost, 3
- blackboost, 2, 3
- ctmboost, 2
- gamboost, 2, 3
- mboost, 2, 3
- mlt, 2, 3
- stmboost, 3